

UNIVERSAL

CHILLING SYSTEMS

UCS-30V AIR COOLED PHYSICAL DATA

Cooling Capacity	kcal/h		93200
	BTU/h		369,900
	Nominal Tonnage	RT	30
	Outlet Water Temp.	°F	50
	Condensation Temp.	°F	122
Power Supply			3PH-480V-60HZ
Max Amp		A	88.0
Total Power Input		HP	67
Power Supply Cable Diameter		mm ²	3×35+2×16
Safety Protection Device			Overload, Inverse Phase, High/Low Pressure, Water Flow, Water Level & Anti-Freeze Protection
Refrigerant	Type		R410A
	Charge	Lbs	80
Compressor	Start Mode		Direct start
	Type		Copeland Fully-Hermetic Scroll Type
	Qty		4
	HP		13.5×4
	RLA (Running Load Amp)		15.1×4
	LRA(Locked Rotor Amp)		125×4
Fan	Qty		6
	Type		External Rotar Axial Fan
	Power	HP	1×6
	Current	A	1.6×6
	LRA	A	9.6×6
	Heat Rejection	BTU	/
	Volume Air Flow	CFM	23500
Condenser	Type		Finned Tubes
	Subcooling	°F	9
	Heat Rejection	BTU	496000
Evaporator	Type		Dry Shell and Tube Type
	Subcooling	°F	9
	Heat Rejection	BTU	369,900
	Cooled Water Flow	GPM	82.0
	Water Pressure Drop	PSI	≤12
Energy Adjust Mode			100%-75%-50%-25%
Throttling Device	Mode		thermal expansion valve
Pipe	Water Outlet		MNPT 3"
	Water Inlet		MNPT 3"

UNIVERSAL

CHILLING SYSTEMS

Water Pump	Flow	GPM	82
	Head	PSI	50.8
	Power	HP	5.5
	LRA	A	48.6
Water Tank	Capacity	GAL	90.6
Sound Pressure	DBA		75
Programming Controller	Display		Touch Screen Digital temperature display microcomputer controller
	Output		GW53
	Output Choice		Relay
	Temp Control Range °F		+41 ~+95
	Temp Control Accuracy°F		±3.6
Dimensions	inches (LxWxH)		107×65×84(For Reference)
Weight	lbs		2970(For Reference)

NOTES:

- 1 Cooling tons based on 10°C (50°F) leaving coolant and 35°C (95°F) ambient air.
Chilled water work allowed temperature range: 5°C~35°C(41°F~95°F).
- 2 Chilled water in and out temperature difference: 3°C~8°C(37.4°F~46.4°F);
Allowed ambient temperature range: -20°C~40°C(-4°F~104°F).
- 3 Power supply:3PH-460V-60Hz, Allowing the voltage fluctuate ±10%, allow phase voltage difference ±2%, Allow the frequency range ±0.2Hz.